# **AD-1688 Specifications**

Applicable devices	Balances and scales with an RS-232C connector manufactured by A&D		
Memory size	Approx. 5,000 data sets in the standard format (15 characters in 1 data set) can be stored		
Clock error	±1 minute / month		
Applicable OS	Windows 2000 / XP / Vista		
Dedicated power supply	ower supply Not required. Power is supplied by the weighing instrument or PC.		
Operating environment	erating environment 5 °C to 40 °C (41 °F to 104 °F), 85 %RH or less (no condensation)		
Dimensions	sions 55 × 103 × 16.5 mm		
Weight	ight Approx. 60 g		

# **Standard Accessories**

USB extension cable (0.5 m) Three RS-232C cables (1 m) with a D-sub 9-pin connector with a D-sub 25-pin connector with a 7-pin DIN connector

The data is stored in CSV format and can be used easily by software such as Microsoft Excel.

E	ile Edit B9	View Insert Fo	rmat <u>I</u> ools <u>D</u>	ata <u>W</u> indo	w <u>H</u> elp	_	8
	A	В	C	D	E	F	-
1	1	6/10/2009	10:41:24	ST	3.076	g	7
2	2	6/10/2009	10:41:36	ST	3.082	g	
3	3	6/10/2009	10:42:06	ST	3.102	g	
4	4	6/10/2009	10:42:38	ST	3.058	g	
5	5	6/10/2009	10:42:55	ST	3.091	g	
6	6	6/10/2009	10:43:01	ST	3.089	g	1
7							7

# Quick USB Adapter AD-85 Transmits weighing data directly from an A&D balance or scale to a USB port of a PC (no driver software is required)\* Quick USB Adapter Sends weighing data to software applications such as Microsoft Excel, Word, and Notepad AD-8527 Small size and IP65 dust and waterproof (with the casing cover) \*Only unidirectional communication from a balance or scale to a PC is possible.

**AD-8527 Specifications** 

Applicable devices	Balances and scales with an RS-232C connector manufactured by A&D			
Dedicated power supply	Not required. Power is supplied by the weighing instrument or PC.			
Operating environment	5 °C to 40 °C (41 °F to 104 °F), 85% RH or less (no condensation)			
Dimensions	55 × 103 × 16.5 mm			
Weight	Approx. 60 g			
Standard accessories	USB extension cable (0.5 m), Three RS-232C cables (1 m)			



# ..Clearly a Better Value

A&D Company, Limited

3-23-14 Higashi-Ikebukuro, Toshima-ku,Tokyo 170-0013 JAPAN Telephone:[81](3) 5391-6132 Fax:[81](3) 5391-6148 http://www.aandd.jp

### A&D ENGINEERING, INC.

1756 Automation Parkway, San Jose, CA 95131 U.S.A. Telephone:[1](408) 263-5333 Fax:[1](408) 263-0119

A&D Australasia Pty Ltd.
32 Dew Street, Thebarton, South Australia 5031 AUSTRALIA Telephone:[61](8) 8301-8100 Fax:[61](8) 8352-7409

# A&D INSTRUMENTS LTD.

Unit 24/26 Blacklands Way Abingdon Business Park, Abingdon, Oxon OX14 1DY UNITED KINGDOM Telephone:[44](1235) 550420 Fax:[44](1235) 550485

## <German Sales Office>

Große Straße 13 b 22926 Ahrensburg GERMANY Telephone:[49](0) 4102 459230 Fax:[49](0) 4102 459231

# Vereyskaya str.17, Moscow, 121357 RUSSIA Telephone: [7] (495) 937-33-44 Fax: [7] (495) 937-55-66 A&D Instruments India Private Limited

A&D RUS CO., LTD.

509 Udyog Vihar Phase V Gurgaon-122 016, Haryana, INDIA Telephone: [91](124) 471-5555 Fax: [91](124) 471-5599

## A&D KOREA Limited

Manhattan Bldg. 8F, 36-2 Yoido-dong, Youngdeungpo-gu, Seoul, KOREA Telephone:[82](2) 780-4101 Fax:[82](2) 782-4280