

U-fixings


Dipped U-bolt series —Soft PVC-coated type—

Electrically insulated U-bolt / Soft PVC-coated type

A10603 Dipped U-bolt (SG)



Coating color: ivory ●



For SGP pipe

Part number A10603 Dipped U-bolt (SG)


Units (mm)

Size code	Size	Nominal diameter	Applicable pipe outer diameter (SG)	Screw diameter	P	H	S	C	L	t
0013	SG- 15	1/2	21.7	W3/8	38	32	25	25	80	2.0
0028	SG- 20	3/4	27.2	W1/2	44	35	25	25	86	2.0
0032	SG- 25	1	34.0	W5/8	50	40	25	25	92	2.0
0047	SG- 32	1 1/4	42.7	W3/4	59	48	30	25	101	2.0
0051	SG- 40	1 1/2	48.6	W7/8	65	51	30	25	107	2.0
0066	SG- 50	2	60.5	W1	77	57	30	25	119	2.0
0085	SG- 65	2 1/2	76.3	W1 1/4	93	70	35	25	135	2.0
0090	SG- 80	3	89.1	W1 1/2	105	77	35	25	148	2.0
0102	SG-100	4	114.3	W1 3/4	130	90	35	25	173	2.0
0117	SG-125	5	139.8	W2	160	110	50	32	213	2.0
0121	SG-150	6	165.2	W2 1/4	186	125	50	32	239	2.0
0136	SG-200	8	216.3	W2 1/2	238	150	50	32	290	2.0

A10605 Dipped U-bolt (CU)



Coating color: black ●



For copper pipe

Part number A10605 Dipped U-bolt (CU)


Units (mm)

Size code	Size	Applicable pipe outer diameter (CU)	Screw diameter	P	H	S	C	L	t
0018	CU- 8	9.53	W1/4	19	19	18	15	45	2.0
0022	CU- 10	12.70	W1/4	22	21	18	15	48	2.0
0037	CU- 15	15.88	W1/4	25	23	20	15	51	2.0
0041	CU- 19	19.05	W1/4	29	25	20	15	55	2.0
0056	CU- 20	22.22	W1/4	32	31	25	15	58	2.0
0179	5 (for air conditioning)	25.40	W1/4	35	33	25	15	61	2.0
0075	CU- 25	28.58	W1/4	38	34	25	15	64	2.0
0080	CU- 32	34.92	W1/4	44	37	25	15	70	2.0
0094	CU- 40	41.28	W1/4	51	40	25	15	77	2.0
0107	CU- 50	53.98	W1/4	63	46	25	15	89	2.0
0111	CU- 65	66.68	W1/4	78	59	30	15	102	2.0
0126	CU- 80	79.38	W1/4	89	64	30	15	115	2.0
0145	CU-100	104.78	W1/4	114	77	30	15	141	2.0
0150	CU-125	130.18	W3/8	143	95	35	25	189	2.0
0164	CU-150	155.58	W1/2	169	107	35	25	214	2.0

A10606 Dipped U-bolt (SU)



Coating color: blue ●



For stainless steel thin-walled pipe (SU)

Part number A10606 Dipped U-bolt (SU)

Units (mm)

Size code	Size	Applicable pipe outer diameter (SU)	Screw diameter	P	H	S	C	L	t
0015	SU- 13	15.88	W1/4	25	23	20	15	51	2.0
0020	SU- 20	22.22	W1/4	32	31	25	15	58	2.0
0034	SU- 25	28.58	W1/4	38	34	25	15	64	2.0
0049	SU- 30	34.00	W3/8	50	40	25	25	92	2.0
0053	SU- 40	42.70	W3/8	59	48	30	25	101	2.0
0068	SU- 50	48.60	W3/8	65	51	30	25	107	2.0
0072	SU- 60	60.50	W3/8	77	57	30	25	119	2.0
0087	SU- 75	76.30	W3/8	93	70	35	25	135	2.0
0091	SU- 80	89.10	W3/8	105	77	35	25	148	2.0
0104	SU-100	114.30	W3/8	130	90	35	25	173	2.0
0119	SU-125	139.80	W1/2	160	110	50	32	213	2.0
0123	SU-150	165.20	W1/2	186	125	50	32	239	2.0
0138	SU-200	216.30	W1/2	238	154	50	32	290	2.0

