



2040B



Standard Double Pitch Sprocket for S Rollers B-type

Order No. Example

2040B 6 1/2



- Chain No.C2040
- Chain Pitch (P)25.4 mm
- Roller Link Inner Width (W) 7.95mm
- Roller Outside Diameter (Dr) 7.92mm
- Tooth Width (T) 7.2 mm

- m Carbon Structural Steel
- h High-frequency Hardened Teeth

Type	No. of Active Teeth	Actual No. of Teeth	Outer Diameter Do	Pitch Diameter Dp	Shaft Hole Diameter d			Boss Diameter BD	Boss Length BL	Weight kg	¥	Semi-F ¥
					Prepared Holes	Minimum	Maximum					
2040B	6 1/2	13	59	54.66	12	13	20	35	22	0.20		
	7 1/2	15	67	62.45	12	13	25	43	22	0.30		
	8 1/2	17	76	70.31	13	14	32	52	22	0.42		
	9 1/2	19	84	78.23	14	15	38	60	25	0.61		
	10 1/2	21	92	86.17	14	15	46	69	25	0.82		
	11 1/2	23	100	94.15	14	15	51	77	25	0.98		
	12 1/2	25	108	102.14	14	15	42	63	25	0.83		



Sprocket No. and Quantity



Same-day shipping



* Since we also manufacture sizes other than those in the catalog, and machine shaft holes/keys/taps, etc., depending on your request, please contact our company's sales office for details.

* Please refer to P24 to P33 for the Semi-F Series <Complete Product> order method.