

単位 (Unit) : mm

直径 DC	全長 LF	溝長 ℓ	先端 PL	在庫 Stock	直径 DC	全長 LF	溝長 ℓ	先端 PL	在庫 Stock	直径 DC	全長 LF	溝長 ℓ	先端 PL	在庫 Stock	直径 DC	全長 LF	溝長 ℓ	先端 PL	在庫 Stock
5.05	150	100	1.5		6.7	125	90	2.0		8.5	400	260	2.6		10.7	200	125	3.2	
5.1	125	80			6.7	150	110			8.6	150	110			10.7	250	150		
5.1	150	110			6.7	200	125			8.6	200	125			10.7	300	175		
5.1	200	125			6.7	250	150			8.6	250	150			10.8	200	125		
5.1	250	150			6.7	300	175			8.6	300	175			10.8	250	150		
5.1	300	175			6.8	125	90			8.7	150	110			10.8	300	175		
5.2	125	80			6.8	150	110			8.7	200	125			10.9	200	125		
5.2	150	110			6.8	200	125			8.7	250	150			10.9	250	150		
5.2	200	125			6.8	250	150			8.7	300	175			10.9	300	175		
5.2	250	150			6.8	300	175			8.8	150	110			11.0	200	125		
5.2	300	175	6.9	125	90	8.8	200	125	11.0	250	150								
5.3	125	80	6.9	150	110	8.8	250	150	11.0	300	175								
5.3	150	110	6.9	200	125	8.8	300	175	11.0	350	210								
5.3	200	125	6.9	250	150	8.9	150	110	11.0	400	260								
5.3	250	150	6.9	300	175	8.9	200	125	11.1	250	150								
5.3	300	175	7.0	125	90	8.9	250	150	11.1	300	175								
5.4	125	80	7.0	150	110	8.9	300	175	11.2	250	150								
5.4	150	110	7.0	200	125	9.0	150	110	11.2	300	175								
5.4	200	125	7.0	250	150	9.0	200	125	11.3	250	150								
5.4	250	150	7.0	300	175	9.0	250	150	11.3	300	175								
5.4	300	175	7.0	350	210	9.0	300	175	11.4	250	150								
5.5	125	80	7.0	400	260	9.0	350	210	11.4	300	175								
5.5	150	110	7.1	150	110	9.1	150	110	11.5	200	125								
5.5	200	125	7.1	200	125	9.1	200	125	11.5	250	150								
5.5	250	150	7.1	250	150	9.1	250	150	11.5	300	175								
5.5	300	175	7.1	300	175	9.1	300	175	11.5	350	210								
5.5	350	210	7.2	150	110	9.1	350	210	11.5	400	260								
5.5	400	260	7.2	200	125	9.2	150	110	11.6	250	150								
5.6	125	80	7.2	250	150	9.2	200	125	11.6	300	175								
5.6	150	110	7.2	300	175	9.2	250	150	11.7	250	150								
5.6	200	125	7.3	150	110	9.2	300	175	11.7	300	175								
5.6	250	150	7.3	200	125	9.3	150	110	11.8	250	150								
5.6	300	175	7.3	250	150	9.3	200	125	11.8	300	175								
5.7	125	80	7.3	300	175	9.3	250	150	11.9	250	150								
5.7	150	110	7.4	150	110	9.3	300	175	11.9	300	175								
5.7	200	125	7.4	200	125	9.4	150	110	12.0	200	125								
5.7	250	150	7.4	250	150	9.4	200	125	12.0	250	150								
5.7	300	175	7.4	300	175	9.4	250	150	12.0	300	175								
5.8	125	80	7.5	150	110	9.4	300	175	12.0	350	210								
5.8	150	110	7.5	200	125	9.5	150	110	12.0	400	260								
5.8	200	125	7.5	250	150	9.5	200	125	12.1	250	150								
5.8	250	150	7.5	300	175	9.5	250	150	12.1	300	175								
5.8	300	175	7.5	350	210	9.5	300	175	12.2	250	150								
5.9	125	80	7.5	400	260	9.5	350	210	12.2	300	175								
5.9	150	110	7.6	150	110	9.5	400	260	12.3	250	150								
5.9	200	125	7.6	200	125	9.6	150	110	12.3	300	175								
5.9	250	150	7.6	250	150	9.6	200	125	12.4	250	150								
5.9	300	175	7.6	300	175	9.6	250	150	12.4	300	175								
6.0	125	90	7.7	150	110	9.6	300	175	12.5	200	125								
6.0	150	110	7.7	200	125	9.7	150	110	12.5	250	150								
6.0	200	125	7.7	250	150	9.7	200	125	12.5	300	175								
6.0	250	150	7.7	300	175	9.7	250	150	12.5	350	210								
6.0	300	175	7.8	150	110	9.7	300	175	12.5	400	260								
6.0	350	210	7.8	200	125	9.8	150	110	12.6	250	150								
6.0	400	260	7.8	250	150	9.8	200	125	12.6	300	175								
6.1	125	90	7.8	300	175	9.8	250	150	12.7	250	150								
6.1	150	110	7.9	150	110	9.8	300	175	12.7	300	175								
6.1	200	125	7.9	200	125	9.9	150	110	12.8	250	150								
6.1	250	150	7.9	250	150	9.9	200	125	12.8	300	175								
6.1	300	175	7.9	300	175	9.9	250	150	12.9	250	150								
6.2	125	90	8.0	150	110	9.9	300	175	12.9	300	175								
6.2	150	110	8.0	200	125	10.0	150	110	13.0	200	125								
6.2	200	125	8.0	250	150	10.0	200	125	13.0	250	150								
6.2	250	150	8.0	300	175	10.0	250	150	13.0	300	175								
6.2	300	175	8.0	350	210	10.0	300	175	13.0	350	210								
6.3	125	90	8.0	400	260	10.0	350	210	13.0	400	260								
6.3	150	110	8.1	150	110	10.0	400	260	13.5	250	150								
6.3	200	125	8.1	200	125	10.1	150	110	13.5	300	200								
6.3	250	150	8.1	250	150	10.1	200	125	14.0	250	150								
6.3	300	175	8.1	300	175	10.1	250	150	14.0	300	200								
6.4	125	90	8.2	150	110	10.1	300	175	14.5	250	150								
6.4	150	110	8.2	200	125	10.2	150	110	14.5	300	200								
6.4	200	125	8.2	250	150	10.2	200	125	15.0	250	150								
6.4	250	150	8.2	300	175	10.2	250	150	15.0	300	200								
6.4	300	175	8.2	350	210	10.2	300	175	16.0	250	150								
6.5	125	90	8.3	150	110	10.3	150	110	16.0	300	200								
6.5	150	110	8.3	200	125	10.3	200	125	17.0	250	150								
6.5	200	125	8.3	250	150	10.3	250	150	17.0	300	200								
6.5	250	150	8.3	300	175	10.3	300	175	18.0	250	150								
6.5	300	175	8.4	150	110	10.4	150	110	18.0	300	200								
6.5	350	210	8.4	200	125	10.4	200	125	19.0	250	150								
6.5	400	260	8.4	250	150	10.4	250	150	19.0	300	200								
6.6	125	90	8.4	300	175	10.4	300	175	20.0	250	150								
6.6	150	110	8.5	150	110	10.5	150	110	20.0	300	200								
6.6	200	125	8.5	200	125	10.5	200	125											
6.6	250	150	8.5	250	150	10.5	250	150											
6.6	300	175	8.5	300	175	10.5	300	175											
6.6	350	210	8.5	350	210	10.6	150	110											
						10.6	200	125											
						10.6	250	150											
						10.6	300	175											

シャンク部の径はドリル直径よりもマイナスに仕上げられています。溝長の長いドリルでは大きなマイナスとなるために、ドリルコレットをご使用の場合には、締め代に余裕があるコレットを選定ください。詳細はI-10を参照ください。

新商品
超硬ドリル
ハイスドリル
タップ
超硬
エンドミル
ハイス
エンドミル
切断工具
パック・
セット商品
その他
精密工具
技術資料
索引