

# Spatter cap

## CP • CPFW



## CPP (Attachable after piping)



### Features

- Protecting PushOne connecting part from spatter, etc
- CCP can be attached after connecting tube.

### Specification

Specification	Product number	Applicable tube outer diameter(mm)	Applicable tube type
Attachment before tube piping	CP4	4	FS
	CP6	6	
	CP8	8	
	CP10	10	
	CP12	12	
Attachment after tube piping	CPFW6	6	FW*FWU
	CPFW8	8	
	CPFW10	10	
	CPFW12	12	
Attachment after tube piping	CPP6	6	FS*FW*FWU
	CPP8	8	
	CPP10	10	
	CPP12	12	

### Reference

- Instruction manual.....P.196

# Tube removing jig (Off tool)

## EOT 6-4



### Features

- Helps removing tube from PushOne

### Applicable tube size


Tube outer diameter : φ4, φ6

### Reference

- Instruction manual.....P.197

# Tube reel

## PTR



### Features

- Easy handling
- Recycled polypropylene resin used

### Specification

Product number	Applicable tube size	Size (mm)				Weight(g)
		(a) Collar width	(b) Reel width	(c) Shaft width	(d) Reel body diameter	
PTR-1	Millimeter size: φ4, 6, 8	(a)	(b)	(c)	(d)	1030
	Inch size : φ1/8, 1/4, 5/16	480	105	50	225	
PTR-2	Millimeter size: φ10, 12	(a)	(b)	(c)	(d)	1170
	Inch size : φ3/8, 1/2	480	210	50	225	

Use PTR-2 for φ8-size FW and FWU tube of 100m long.

### Handling instructions

- ⚠ **Caution** The tube reel cannot be used with other manufacturers' tubes.
- ⚠ **Caution** The tube reel is made of resin and may be cracked if dropped or hit hard. Careful handling is required.
- ⚠ **Caution** You may need to widen the inner drum to set a tube if the wound tube bundle is deformed.

### Reference

- Instruction manual.....P.194