


G-LIST No TH1185

ポイントタップ ロングシャンク SPIRAL POINTED TAP WITH LONG SHANK



A-LT-POT



●マークの説明はP.2をご覧ください。
See page 2 for explanation of icons.

FROM

単位:mm Unit:mm

ツールNo. EDP NO.	呼び Thread Size	精度表記 Grade	精度 TAP Limit	食付 ℓc	全長 L	ねじ長 ℓ	首下長 ℓn	シャンク径 Ds	溝数 Flutes	突き出し センチ External Centre	在庫 Stock	重量 Weight	標準価格 (Yen)
8326042		STD	OH3	5P	100	41	41	7	3	D		37	5,540
8326043	M 10 x 1				150	24	60	54				7,900	
8326040	M 10 x 0.75				100	41	41	38				6,400	
8326041					150	24	60	54				9,400	
8326052	M 11 x 1.5				100	48	48	48				5,580	
8326053					150	25	60	67				8,100	
8326092	M 11 x 1.25				100	48	48	48				6,370	
8326093					150	25	60	67				8,100	
8326050					100	48	48	49				6,770	
8326051	M 11 x 1				150	25	60	68				10,200	
8326048					100	48	48	50				7,460	
8326049	M 11 x 0.75				150	25	60	69				11,400	
8326060					100	48	48	54				5,660	
8326061	M 12 x 1.75				150	29	60	76				8,030	
8326058					100	48	48	54				5,660	
8326059	M 12 x 1.5				150	29	60	75				8,030	
8326056					100	48	48	54				5,660	
8326057	M 12 x 1.25				150	29	60	75				8,030	
8326054					100	48	48	56				6,400	
8326055	M 12 x 1				150	29	60	77				9,330	
8326065		100	48	48	110	10,800							
8326064	M 14 x 1.5	150	30	60	110	10,800							
8326063		100	48	48	109	13,100							
8326062	M 14 x 1	150	30	60	109	13,400							
8326067		100	48	48	115	12,800							
8326066	M 15 x 1.5	150	32	60	116	13,900							
8326070		100	48	48	152	11,300							
8326071	M 16 x 2	200	32	80	202	13,800							
8326069		150	32	60	154	11,300							
8326068	M 16 x 1	150	32	60	153	13,600							
8326073		150	37	60	169	17,100							
8326072	M 17 x 1	150	37	60	169	19,600							
8326077		150	37	60	190	14,100							
8326076	M 18 x 2	150	37	60	189	16,100							
8326075		150	37	60	191	14,100							
8326074	M 18 x 1.5	150	37	60	193	20,600							
8326081		150	37	60	222	17,100							
8326082	M 20 x 2.5	200	37	80	292	20,600							
8326080		150	37	60	220	21,200							
8326079	M 20 x 1.5	150	37	60	224	17,100							
8326078		150	37	60	225	22,700							
8326086	M 22 x 2.5	150	38	63	277	19,500							
8326085		150	38	63	277	24,100							
8326084	M 22 x 1.5	150	38	63	282	19,500							
8326083		150	38	63	280	25,500							
8326090	M 24 x 3	150	45	66	341	22,600							
8326091		200	45	66	456	24,600							
8326089	M 24 x 2	150	45	66	340	28,200							
8326088		150	45	66	342	22,600							
8326087	M 24 x 1	150	45	66	345	30,500							

■ 突き出しセンチ長さ・シャンク四角部寸法 ℓk , KはP.890をご覧ください。

1. 精度欄 \square は2級めねじ相当適応のタップ推奨精度です。(P.706参照)
2. タップ精度はめねじ精度を保証するものではありません。
3. 送りの不安定な機械で使用しますと、めねじ拡大トラブルが発生する場合がありますのでご注意ください。
4. 再研磨はお勧めしておりません。

■ Please see page 890 for length of external centre and shank square length (ℓk) and width (K).

1. The recommended tap limit corresponds to JIS class 2 internal thread standard. (see page 706)
2. Tap limit does not guarantee thread limit for the internal thread after tapping.
3. Stable feed control machines are recommended to avoid over size tapping.
4. Regrinding is not recommended.

NEXT

A, B, C, D=標準在庫品 A, B, C, D=Standard stock item.

\square =特定代理店在庫品 \square =Stocked by specific distributors. Contact us for price & availability.