


G-LIST No TH1036

ステンレス用 ロングシャンク LONG SHANK FOR STAINLESS STEELS

EX-LT-SUS-POT



●マークの説明はP.2をご覧ください。  
See page 2 for explanation of icons.

単位:mm Unit:mm

ツールNo. EDP NO.	呼び Thread Size	精度 Grade	食付 TAP Limit	全長 $\ell_c$	ねじ長 L	首下長 $\ell$	シャンク長 $\ell_n$	シャンク径 Ds	溝数 Flutes	突出しセンタ Grand Centre	在庫 Stock	重量 Weight	標準価格 (Yen)
15801	M 3 x0.5	STD	OH2	100	11	19	4	3	D	有	11	3,060	
15803	150			有	15	5,440							
15805	100			有	16	2,740							
15807	150			有	23	5,140							
15809	100			有	19	2,350							
15811	M 5 x0.8	4P	OH2	100	16	24	5.5	3	D	有	28	3,930	
15813	150			有	23	2,040							
15815	100			有	19	2,900							
15818	150			有	33	3,630							
15820	100			有	28	2,560							
15822	M 8 x1.25	STD	OH3	100	22	37	6.2	3	D	有	40	4,400	
15827	150			有	36	3,160							
15829	100			有	51	5,140							
15832	150			有	37	3,160							
15834	100			有	52	5,140							
15843	M10 x1.5	STD	OH3	100	24	41	7	3	D	有	75	6,550	
15844	150			有	96	7,700							
15832	100			有	37	3,160							
15834	150			有	52	5,140							
15843	100			有	75	6,550							
15844	M12 x1.75	STD	OH4	100	29	48	8.5	3	D	有	96	7,700	
15848	150			有	96	7,700							
15832	100			有	37	3,160							
15834	150			有	52	5,140							
15843	100			有	75	6,550							
15848	M12 x1.5	STD	OH4	100	29	48	8.5	3	D	有	96	7,700	
15848	150			有	96	7,700							
15832	100			有	37	3,160							
15834	150			有	52	5,140							
15843	100			有	75	6,550							

ツールNo. EDP NO.	呼び Thread Size	精度 Grade	食付 TAP Limit	全長 $\ell_c$	ねじ長 L	首下長 $\ell_n$	シャンク径 Ds	溝数 Flutes	突出しセンタ External Centre	在庫 Stock	重量 Weight	標準価格 (Yen)
15849	M12 x1.5	STD	OH3	200	29	48	8.5	3	D	有	95	7,970
15853	150			有	74	6,550						
15854	200			有	96	7,970						
15860	150			有	108	8,180						
15861	200			有	141	9,930						
15864	M14 x2	4P	OH3	150	30	48	10.5	3	D	有	107	8,180
15865	200			有	142	9,930						
15868	150			有	201	11,500						
15872	200			有	201	11,500						
15875	200			有	250	15,000						
15878	M18 x2.5	STD	OH4	200	37	55	14	3	D	有	242	15,000
15881	200			有	287	18,900						
15884	200			有	281	18,900						
15887	200			有	362	20,400						
15890	200			有	361	20,400						
15893	M20 x2.5	STD	OH4	200	37	58	15	3	D	有	287	18,900
15896	200			有	281	18,900						
15893	200			有	362	20,400						
15896	200			有	446	23,500						
15896	200			有	435	23,500						

■突出しセンタ長さ・シャンク四角部寸法  $\ell_k$ , KはP.890をご覧ください。

1. 精度欄    は2級めねじ相当適応のタップ推奨精度です。(P.706参照)
2. タップ精度はめねじ精度を保証するものではありません。
3. 切削油剤、ペーストはP.868をご参照下さい。

■ Please see page 890 for length of external centre and shank square length  $\ell_k$  and width K.

1. The recommended TAP Limit corresponds to JIS class 2 internal thread standard. (see page 706)
2. TAP Limit does not guarantee thread limit for the internal thread after tapping.
3. Cutting fluid and Paste : Please refer to P.868.

形状寸法表

タップ

ポイントタップシリーズ

OZTツールプリセッター OZT Tool Presetter

**迅速で高精度な測定！**  
**外段取りで生産効率アップ！**

※詳細は **▶P.888** を参照ください。  
Please refer **P.888** for the details

低炭素鋼	中炭素鋼	高炭素鋼	合金鋼	調質鋼	ステンレス鋼	工具鋼	鋳鋼	鋳鉄	ダクタイル鋳鉄	銅	黄銅	黄銅鋳物	青銅	アルミ圧延材	アルミ合金鋳物	マグネシウム合金鋳物	亜鉛合金鋳物	チタン合金	Ni基合金	熱硬化性プラスチック	熱可塑性プラスチック	
Low Carbon Steel	Medium Carbon Steel	High Carbon Steel	Alloy Steel	Hardened Steel	Stainless Steel	Tool Steel	Cast Steel	Cast Iron	Ductile Cast Iron	Copper	Brass	Brass Casting	Bronze	Aluminum Rolled	Aluminum Alloy Casting	Magnesium Alloy Casting	Zinc Alloy Casting	Titanium Alloy	Nickel Alloy	Thermo Setting Plastic	Thermo Plastic	
C ~0.25%	C0.25% ~0.45%	C 0.45% ~	SCM	25~45 HRC	45~55 HRC	50~60 HRC	SUS	SKD	SC	FC	FCD	Cu	Bs	BsC	PB	AL	AC,ADC	MC	ZDC			
							◎					◎										◎

A, B, C, D=標準在庫品 A, B, C, D=Standard stock item.  
 =特定代理店在庫品  =Stocked by specific distributors. Contact us for price & availability.