2-Color Indicator Reed Auto Switch Tie-rod Mounting Type **D-A59W**

Grommet

The proper operating range can be determined by the color of the light.

 $(Red \rightarrow Green \leftarrow Red)$



Auto Switch Specifications

Refer to SMC website for the details of the products conforming to the international standards.

	PLC: Programmable Logic Controller	
D-A59W (With indicator light)		
Auto switch model	D-A59W	
Applicable load	Relay, PLC	
Load voltage	24 VDC	
Load current range(3)	5 to 40 mA	
Circuit diagram*	6	
Contact protection circuit	Built-in	
Internal voltage drop	4 V or less	
Indicator light	Operating range ········· Red LED illuminates. Proper operating range ······· Green LED illuminates.	
Standard	CE marking	

Oilproof Heavy-duty Lead Wire Specifications

Auto switch model		D-A59W
Sheath	Outside diameter [mm]	ø4
Insulator	Number of cores	2 cores (Brown/Blue)
	Outside diameter [mm]	ø1.22
Conductor	Effective area [mm²]	0.3
	Strand diameter [mm]	ø0.08
Lead wire minimum bending radius [mm] (Reference values)		24

* Refer to the circuit diagram no. on page 1587.
Note 1) Refer to page 1584 for reed auto switch common specifications.
Note 2) Refer to page 1584 for lead wire lengths.
Note 3) Under 5 mA, the strength of the indicator light is poor. In some cases, visibility of the indicator light will not be possible where the output signal is less than 2.5 mA. However, there is no problem in terms of contact output, when an output signal exceeds 1 mA or

Weight

(g)

Auto switch model		D-A59W
Lead wire length	0.5 m (Nil)	25
	3 m (L)	80

Dimensions

(mm)





