

**Dimensions**

**Branch Tee: KFT**




Resin sleeve



Brass sleeve

Applicable tubing size (mm)		Con- nection thread R	Model	Width across flats		L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>4</sub>	M	ød	A*	Effective area (mm <sup>2</sup> )	Weight (g)				
O.D.	I.D.			H <sub>1</sub>	H <sub>2</sub>													
ø4	ø2.5	R1/8	KFT04-01S	10	10	27.5	20.8	17	13	15.5	1.5	19.3	3	29				
		R1/4	KFT04-02S					19						34				
		R1/8	KFT04B-01S					17						30				
		R1/4	KFT04B-02S					19						35				
ø6	ø4	R1/8	KFT06-01S	10	10	27.2	20.5	17	13	15.2	3	19.3	10	32				
		R1/4	KFT06-02S					19						37				
		R3/8	KFT06-03S	12	12	30.2	23.5	22	15.7	23	12	53						
		R1/8	KFT06B-01S	10	10	24.2	21.2	17	13	12.2	3	19.3	10	34				
		R1/4	KFT06B-02S					19						39				
		R3/8	KFT06B-03S	12	12	27.2	24.2	22	15.7	23	12	55						
ø8	ø5	R1/8	KFT08U-01S	12	14	30.2	23.5	20	16	16.2	4	23.3	14	49				
		R1/4	KFT08U-02S					23						17	24.3	19	50	
		R3/8	KFT08U-03S					22						15.7	23	16	56	
	ø6	R1/8	KFT08N-01S	12	14	27.3	24.3	20	16	13.3	5	24.3	25	49				
		R3/8	KFT08N-03S					22							15.7	23	16	54
		R1/8	KFT08B-01S					20							16	23.3	16	48
ø10	ø6.5	R1/4	KFT10U-02S	12	17	31.8	24.5	23	17	18.8	5.5	24.3	27	46				
		R3/8	KFT10U-03S					22						15.7	23	34	63	
		R1/2	KFT10U-04S					14						33.8	26.5	27	18.8	27.3
	ø7.5	R1/4	KFT10N-02S	12	17	31.8	24.5	23	17	15.0	6.5	24.3	30	57				
		R3/8	KFT10N-03S					22							15.7	23	30	62
		R1/2	KFT10N-04S					14							33.8	26.5	27	18.8
ø12	ø8	R1/4	KFT10B-02S	12	17	28.0	25.0	23	17	15.0	6.5	24.3	30	60				
		R3/8	KFT10B-03S					22							15.7	23	30	65
		R1/2	KFT10B-04S					14							30.0	27.0	27	18.8
	ø9	R1/4	KFT12U-02S	14	19	34.3	27.5	25	19	19.3	7	26.2	44	78				
		R3/8	KFT12U-03S					24							17.7	27.3	32	75
		R1/2	KFT12U-04S					14							34.3	27.5	27	18.8
ø12	R1/4	KFT12N-02S	14	19	30.6	27.6	25	19	15.5	8	27.5	32	78					
	R3/8	KFT12N-03S					24							17.7	27.3	32	78	
	R1/2	KFT12N-04S					14							30.6	27.6	27	18.8	27.3
R1/4	KFT12B-02S	14	19	30.6	27.6	25	19	15.5	8	27.5	32	78						
R3/8	KFT12B-03S					24							17.7	27.3	48	96		
R1/2	KFT12B-04S	14	30.6	27.6	27	18.8	27.3	48	96									



\* Reference dimensions after installation of R thread.

KQ2

KQB2

KS  
KX

KM

**KF**

M

H/DL  
L/LL

KC

KK

KK130

DM

KDM

KB

KR

KA

KQG2

KG

KFG2

MS

KKA

KP

LQ

MQR

T

IDK