

**Dimensions**

**Male Run Tee: KFY**




Resin sleeve



Brass sleeve

Applicable tubing size (mm)		Conne- ction thread R	Model	Width across flats		L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L <sub>4</sub> <sup>*</sup>	M	ød	A <sup>*</sup>	Effective area (mm <sup>2</sup> )	Weight (g)							
O.D.	I.D.			H <sub>1</sub>	H <sub>2</sub>																
ø4	ø2.5	R1/8	KFY04-01S	10	10	27.5	20.8	17	13	15.5	1.5	40.5	3.5	28							
		R1/4	KFY04-02S												24.4	21.4	19	12.4	37.4	32	
		R1/8	KFY04B-01S																		19
		R1/4	KFY04B-02S																		
ø6	ø4	R1/8	KFY06-01S	10	12	27.2	20.5	17	13	15.2	3	40.2	11	31							
		R1/4	KFY06-02S												19	37					
		R3/8	KFY06-03S	12	30.2	23.5	22	15.7	45.8	13	51										
		R1/8	KFY06B-01S									10	12	24.2	21.2	19	13	12.2	37.2	11	33
		R1/4	KFY06B-02S	19	39																
		R3/8	KFY06B-03S			12	27.2	24.2	22	15.7	42.8	13	53								
ø8	ø5	R1/8	KFY08U-01S	12	14	30.2	23.5	20	16	16.2	4	46.2	15	48							
		R1/4	KFY08U-02S					23	17			47.2	21	50							
		R3/8	KFY08U-03S					22	15.7			45.8	21	55							
		R1/8	KFY08N-01S					20	16			46.2	18	47							
	ø6	R1/4	KFY08N-02S					23	17		47.2	27	48								
		R3/8	KFY08N-03S					22	15.7		45.8	27	53								
		R1/8	KFY08B-01S					20	16		43.3	18	49								
		R1/4	KFY08B-02S					27.3	24.3		23	17	44.3	27	50						
R3/8	KFY08B-03S	22	15.7	42.9	27	55															
ø10	ø6.5	R1/4	KFY10U-02S	12	17	31.8	24.5	22	15.7	18.8	5.5	48.8	30	58							
		R3/8	KFY10U-03S									22	15.7	47.4	38	63					
		R1/2	KFY10U-04S														33.8	26.5	27	18.8	52.6
	ø7.5	R1/4	KFY10N-02S					14	17		31.8	24.5	23	17	15.0	6.5	48.8	33	57		
		R3/8	KFY10N-03S														22	15.7	47.4	46	62
		R1/2	KFY10N-04S																		
ø12	ø8	R1/4	KFY10B-02S	12	17	28.0	25.0	23	17	19.3	8	45.0	33	60							
		R3/8	KFY10B-03S									22	15.7	43.6		46	65				
		R1/2	KFY10B-04S					30.0	27.0									27	18.8	48.8	91
		R1/4	KFY12U-02S					14	19			34.3	27.5	25	19	53.3	34	7	53.3	34	79
	R3/8	KFY12U-03S	24	17.7	51.9	49	79														
	R1/2	KFY12U-04S									27			18.8	53.1				93		
	R1/4	KFY12N-02S	25	19	53.3	36	76														
	ø9	R3/8	KFY12N-03S	14	19	30.6	27.6	24	17.7		15.5	8	8	51.9	54	78					
R1/2		KFY12N-04S	27							18.8				53.1	92						
R1/4		KFY12B-02S						25	19							49.6	36	79			
R3/8		KFY12B-03S	24					17.7	48.2	54				81							
R1/2	KFY12B-04S	27		18.8	49.4	95															



\* Reference dimensions after installation of R thread.

- KQ2
- KQB2
- KS  
KX
- KM
- KF**
- M
- H/DL  
L/L
- KC
- KK
- KK130
- DM
- KDM
- KB
- KR
- KA
- KQG2
- KG
- KFG2
- MS
- KKA
- KP
- LQ
- MQR
- T
- IDK