

KR-W2 Series


Male Run Tee: KRY-W2



Applicable tubing O.D. (mm)	Connection thread R	Model	H (width across flats)	⁽¹⁾		L1	L2	A *	M	Effective area (mm ²)		Weight (g)
				øD1	øD2					FR double layer	FR soft nylon	
6	1/8	KRY06-01SW2	10	12.8	10	20	22.1	39	17	10.6	6.4	12
	1/4	KRY06-02SW2	14				26.5	41				20
	3/8	KRY06-03SW2	17				27.9	42.5				34
8	1/8	KRY08-01SW2	12	15.2	12	23	23.6	43.5	18.5	25.6	17.7	14
	1/4	KRY08-02SW2	14				28	45.5				22
	3/8	KRY08-03SW2	17				29.4	47				36
10	1/8	KRY10-01SW2	17	18.5	17	26.5	26.1	49.5	21	40.0	28.4	31
	1/4	KRY10-02SW2					29.5	50.5				29
	3/8	KRY10-03SW2					30.9	52				39
12	1/4	KRY12-03SW2	22	20.9	17	28.5	35.1	54.5	22	57.4	45.4	41
	3/8	KRY12-03SW2	17				31.9	55				41
	1/2	KRY12-04SW2	22				36.1	57.5				68

* Reference dimensions after R thread installation.

Note 1) øD: Max. diameter




Branch: KRU-W2



Applicable tubing O.D. (mm)	Connection thread R	Model	H (width across flats)	⁽¹⁾		L	P	A *	M	Effective area (mm ²)		Weight (g)		
				øD1	L					FR double layer	FR soft nylon			
6	1/8	KRU06-01SW2	13	12.8	44.6	12.8	43	41.5	17	10.4	4.2	12		
	1/4	KRU06-02SW2	14									48.5	43	22
	3/8	KRU06-03SW2	17									49.9	44.5	35
8	1/8	KRU08-01SW2	14	15.2	55	15.2	49.5	48.5	18.5	25.6	17.7	16		
	1/4	KRU08-02SW2	17									51.6	48.5	24
	3/8	KRU08-03SW2	19									55.4	50	36
10	1/4	KRU10-02SW2	19	18.5	60.9	18.5	55.5	55	21	40	28.4	30		
	1/2	KRU10-04SW2	22									64.1	57	40
	3/8	KRU10-03SW2	17									60.9	50	36
12	1/4	KRU12-02SW2	22	20.9	64.4	20.9	59	58.5	22	57.4	45.4	41		
	3/8	KRU12-03SW2	17									67.6	60.5	41
	1/2	KRU12-04SW2	22									67.6	60.5	65

* Reference dimensions after R thread installation.

Note 1) øD: Max. diameter




Union "Y": KRU-W2



Applicable tubing O.D. (mm)	Model	⁽¹⁾ øD	L1	L2	P	Q	M	Effective area (mm ²)		Weight (g)
								FR double layer	FR soft nylon	
6	KRU06-00W2	12.8	37	20	12.8	11.7	17	10.4	4.2	10
8	KRU08-00W2	15.2	42.5	24.5	15.2	13.7	18.5	25.6	17.7	12
10	KRU10-00W2	18.5	48	27.5	18.5	16.1	21	40	28.4	16
12	KRU12-00W2	20.9	51	30	20.9	18.1	22	57.4	45.4	23

Note 1) øD: Max. diameter



Plug-in "Y": KRU-W2



Applicable tubing O.D. (mm)	Applicable fitting size ød	Model	⁽¹⁾ øD	L1	L2	P	Q	A	M	Effective area (mm ²)		Weight (g)
										FR double layer	FR soft nylon	
6	6	KRU06-99W2	12.8	55.5	20	12.8	11.7	38.5	17	10.4	4.2	19
8	8	KRU08-99W2	15.2	64.5	24.5	15.2	13.7	46	18.5	25.6	17.7	22
10	10	KRU10-99W2	18.5	71.5	27.5	18.5	16.1	50.5	21	40	28.4	26
12	12	KRU12-99W2	20.9	75.5	30	20.9	18.1	53.5	22	57.4	45.4	32

Note 1) øD: Max. diameter

