



33	31.05	29	528073010	30
32	30.05	28	528072910	29
31	29.05	27	528072810	28
30	28.05	26	528072710	27
29	27.05	25	528072610	26
28	26.05	24	528072510	25
27	25.05	23	528072410	24
26	24.05	22	528072310	23
25	23.05	21	528072210	22
24	22.05	20	528072110	21
23	21.05	19	528072010	20
22	20.05	18	528071910	19
21	19.05	17	528071810	18
20	18.05	16	528071710	17
19	17.05	15	528071610	16
18	16.05	14	528071510	15
17	15.05	13	528071410	14
16	14.05	12	528071310	13
15	13.05	11	528071210	12
14	12.05	10	528071110	11
13	11.05	9	528071010	10
12	10.05	8	528070910	9
11	9.05	7	528070810	8
10	8.05	6	528070710	7
9	7.05	5	528070610	6
8	6.05	4	528070510	5
7	5.05	3	528070410	4
6	4.05	2	528070310	3
C	B	A	ENG. NO.	極数 CIRCUIT

無鉛
LEAD FREE

- 注記 NOTES**
- 1. 回路番号 1 を基準に奇数番目の極におけるソルダータール。
ODD NUMBER SOLDER TAIL FROM THE CKT. NO. 1.
 - 2. 回路番号 1 を基準に偶数番目の極におけるソルダータール。
EVEN NUMBER SOLDER TAIL FROM THE CKT. NO. 1.
 - 3. キングはソルダータール全極にもらう。
SOLDER TAIL KINK SHALL BE PROVIDED ON ALL TAILS.
 - 4. 偶数極に適用。
APPLY FOR EVEN CKT..

材料
MATERIAL
ハウジング : PPS UL 94V-0
ハウジング : PPS UL 94V-0
ターミナル : りん青銅 錫メッキ t=0.25
TERMINAL : PHOS-BRO., TIN-PLATED

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC NO. 108E19 DRWN. GB CHKD. KATAHASHI APPR. TKUSUHARA01 REV.	GENERAL TOLERANCES (UNLESS SPECIFIED) ANGULAR TOL ± 3.0 °	DIMENSION UNITS: MM SCALE: 10:1	molex 1.0 FFC CONN. NON Z.I.F. DIP R/A PRODUCT CUSTOMER DRAWING	
	4 PLACES ± 0.2 3 PLACES ± 0.2 2 PLACES ± 0.25 1 PLACE ± 0.3 0 PLACES ± 0.3	DRWN BY: GB DATE: 2016/01/12 CHKD BY: KATAHASHI DATE: 2016/09/28 APPR BY: TKUSUHARA01 DATE: 2016/09/29		SERIES: 52807 MATERIAL NUMBER: SEE CHART CUSTOMER: GENERAL
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DRAWING SIZE: A3 THIRD ANGLE PROJECTION		DOCUMENT NUMBER: 528071000 DOC TYPE: PSD DOC PART: 000 SHEET NUMBER: 1 OF 2
	RELEASE STATUS: P1 RELEASE DATE: 29.09.2016 01:01:38			