
Cylinder Gauges (Blind Hole Type)

CG series

If using a CC type cylinder gauge for blind hole bore diameter, its guide plate interrupt the measurement at a point deeper than "T", as shown in the figure below.

In such case, the CG type with modified guide plate is suitable for measurement of the diameter to the point as deep as "t".



- ** Dial gauge is not furnished and supplied only on request. Suitable dial gauges are 17Z, 57B (0.01mm) and 15Z, 5F (0.001mm).
- * CG-3C includes 50 mm extension collar.
- * In general, it is the range from the origin, that is the position where the plunger is pushed in by 0.1 mm, to the position where the plunger is pushed in further by 1.2 mm.

List of special length below grip (available on request)

	L=50 (mm)	L=100 (mm)	L=150 (mm)	L=200 (mm)	L=250 (mm)	L=300 (mm)	L=400 (mm)	L=500 (mm)	L=600 (mm)	L=700 (mm)	L=800 (mm)	L=900 (mm)	L=1000 (mm)
CG-01	0	standard	0	<u> </u>	0	0							
CG-1	0	0	standard	0	0	0	0	0					
CG-2	0	0	standard		0	0	0	0		0	0	0	0
CG-3	0	0	standard	0	0	0	0	0	0	0	0	0	0
CG-3C		0	standard		0		0						0
CG-4	0	0	0	0	standard	0	0	0	0	0	0	0	0
CG-5		0	0		standard	0	0	0		0	0	0	0
CG-6	0	0	0	0	0	0	standard	0	0	0	0	0	0