

Pressure Gauge for Vacuum

GZ46/GZ46E Series



GZ46

GZ46-2

⚠ Specific Product Precautions

Be sure to read this before handling the products. Refer to back page 50 for safety instructions.

Selection

⚠ Caution

1. Make sure that no direct impact or vibrations are applied to the body.
2. If operating under pressure pulsations or in high frequency operations, please contact SMC.

Mounting

⚠ Caution

1. During transport and installation, do not apply shock to the product, such as by dropping doing so will affect its precision.
2. Regarding the installation posture, place it perpendicular to the ground, with the zero point on the reading of a pressure gauge facing down.
3. Do not install it in an area that is exposed to high temperature or humidity, because doing so will lead to improper operation.
4. To screw in the pressure gauge, make sure to turn the gauge by placing a wrench over the square wrench flats.

If the pressure gauge is screwed in by holding it on some other area, air leakage or damage may result.

Standard Specifications

Model		GZ46	GZ46E
Type	Back side thread		
Port size ⁽¹⁾	R 1/8, R 1/4 (Option: M = M5 x with thread)		
Fluid ^{(2) (5)}	Air		
Indication precision ⁽⁶⁾	±3%		
Bourdon tube part cleaning	—		Wetted parts degrease washing
Material ⁽⁴⁾	Case (Surface treatment)	Rolled steel (Black melamine painted)	
	Clear cover (Surface treatment)	Polycarbonate Part no.: G46-00-00-3	Polycarbonate (Hard coated) Part no.: G46-00-00-2
	Stud (Surface treatment)	Brass	Brass (Electroless nickel plated) ⁽³⁾
	Bourdon tube	Brass	
Weight [kg]	0.078		0.08
Attachment:	C	Part no.: 1305104-1A	
With cover ring assembly	C1	Part no.: 1305104-3A	
	C2	Part no.: 1305104-9A	

Note 1) When mounting a pressure gauge, use caution not to tighten excessively. Excessive tightening will cause product failure. Use a pipe tape for sealing.

Note 2) When using other fluids, please consult with SMC for fluid compatibility information concerning corrosive potential.

Note 3) Movable parts (gear and etc.) in the pressure gauge are made of brass.

Note 4) Wetted parts stainless steel specifications are not available.

Note 5) Avoid freezing as this may cause a malfunction.

Note 6) The guaranteed temperature range is 23°C ±5°C.

Model (Standard)

Model	Pressure range ⁽¹⁾	Indication unit	Connection thread	Note
	kPa			
GZ46-K-01 to 02	-100 to 0	kPa	R 1/8, 1/4	—
GZ46-K-01 to 02-C/C1/C2	-100 to 0	kPa	R 1/8, 1/4	With cover ring assembly
GZ46-K-01 to 02M	-100 to 0	kPa	R 1/8, 1/4 M5 (Female thread)	—
GZ46E-K-01 to 02M	-100 to 0	kPa	R 1/8, 1/4 M5 (Female thread)	—
GZ46-K2K-01 to 02	-100 to 200	kPa	R 1/8, 1/4	—

Note 1) Do not apply more excessive pressure than max. pressure display. It will be a cause of malfunction.

Model (Made to Order)

Please consult with SMC for models other than shown below, as delivery times may be extended.

Model	Pressure range ⁽¹⁾	Indication unit	Connection thread	Note
	kPa			
GZ46-K1K-01 to 02	-100 to 100	kPa	R 1/8, 1/4	—

Note 1) Do not apply more excessive pressure than max. pressure display. It will be a cause of malfunction.