

呼稱 호칭 Model	外径 외경(mm) Outer Dia.	内径 내경(mm) Inner Dia.	自由長 자유길(mm) Free length	定数 정수(kg/mm) spring constant	30万 (0.3million)		50万 (0.5 million)		100万 (1 million)	
					变形量 변형량(mm) Deflection	荷重 하중(kgf) Load	变形量 변형량(mm) Deflection	荷重 하중(kgf) Load	变形量 변형량(mm) Deflection	荷重 하중(kgf) Load
SL 6 × 15	6	3	15	1.33	6.0	8	5.4	7.2	4.8	6.4
20			20	1.00	8.0		7.2		6.4	
25			25	0.80	10.0		9.0		8.0	
30			30	0.67	12.0		10.8		9.6	
35			35	0.57	14.0		12.6		11.2	
40			40	0.50	16.0		14.4		12.8	
45			45	0.44	18.0		16.2		14.4	
50			50	0.40	20.0		18.0		16.0	
55			55	0.36	22.0		19.8		17.6	
60			60	0.33	24.0		21.6		19.2	
65			65	0.31	26.0		23.4		20.8	
70			70	0.29	28.0		25.2		22.4	
SL 8 × 10			8	4	10		2.50		4.0	
15	15	1.67			6.0	5.4	4.8			
20	20	1.25			8.0	7.2	6.4			
25	25	1.00			10.0	9.0	8.0			
30	30	0.83			12.0	10.8	9.6			
35	35	0.71			14.0	12.6	11.2			
40	40	0.63			16.0	14.4	12.8			
45	45	0.56			18.0	16.2	14.4			
50	50	0.50			20.0	18.0	16.0			
55	55	0.46			22.0	19.8	17.6			
60	60	0.42			24.0	21.6	19.2			
65	65	0.38			26.0	23.4	20.8			
70	70	0.36			28.0	25.2	22.4			
SL 10 × 10	10	5	10	3.61	4.0	14.5	3.6	13	3.2	11.5
15			15	2.41	6.0		5.4		4.8	
20			20	1.81	8.0		7.2		6.4	
25			25	1.45	10.0		9.0		8.0	
30			30	1.21	12.0		10.8		9.6	
35			35	1.03	14.0		12.6		11.2	
40			40	0.90	16.0		14.4		12.8	
45			45	0.80	18.0		16.2		14.4	
50			50	0.73	20.0		18.0		16.0	
55			55	0.66	22.0		19.8		17.6	
60			60	0.60	24.0		21.6		19.2	
65			65	0.55	26.0		23.4		20.8	
70			70	0.51	28.0		25.2		22.4	
			75	0.48	30.0	27.0	24.0			
			80	0.45	32.0	28.8	25.6			
			90	0.40	36.0	32.4	28.8			
			100	0.36	40.0	36.0	32.0			