

重荷重
중하중
HEAVY LOAD

SH

하중 荷重 ±10%
직각도 直角度 2° 以下
자유장 自由長 50m/m 以下 ±0.5m/m
55m/m 以上 ± 1%

呼び 호칭 Model	外径 외경(mm) Outer Dia.	内径 내경(mm) Inner Dia.	自由長 자유장(mm) Free length	定数 정수(spring constant)	30万 (0.3million)		50万 (0.5 million)		100万 (1 million)						
					変形量 변형량(mm) Deflection	荷重 하중(kg) Load	変形量 변형량(mm) Deflection	荷重 하중(kg) Load	変形量 변형량(mm) Deflection	荷重 하중(kg) Load					
SH 6×15	6	3	15	3.90	3.6	14	3.2	13	2.9	11					
20			20	2.90	4.8		4.3		3.8						
25			25	2.30	6.0		5.4		4.8						
30			30	1.90	7.2		6.5		5.8						
35			35	1.70	8.4		7.6		6.7						
40			40	1.50	9.6		8.6		7.7						
45			45	1.30	10.8		9.7		8.6						
50			50	1.20	12.0		10.8		9.6						
55			55	1.10	13.2		11.9		10.6						
60			60	1.00	14.4		13.0		11.5						
65			65	0.90	15.6		13.8		12.48						
70			70	0.83	16.8		14.9		13.44						
SH 8×10			8	4	10		8.80		2.4		21	2.2	19	1.9	17
15					15		5.86		3.6			3.2		2.9	
20	20	4.40			4.8	4.3	3.8								
25	25	3.52			6.0	5.4	4.8								
30	30	2.93			7.2	6.5	5.8								
35	35	2.51			8.4	7.6	6.7								
40	40	2.20			9.6	8.6	7.7								
45	45	1.95			10.8	9.7	8.6								
50	50	1.76			12.0	10.8	9.6								
55	55	1.60			13.2	11.9	10.6								
60	60	1.47			14.4	13.0	11.5								
65	65	1.35			15.6	14.0	12.5								
70	70	1.26			16.8	15.1	13.4								
75	75	1.17			18.0	16.2	14.4								
SH 10×10	10	5	10	12.27	2.4	30	2.2	27	1.9	24					
15			15	8.18	3.6		3.3		2.9						
20			20	6.25	4.8		4.3		3.8						
25			25	5.00	6.0		5.4		4.8						
30			30	4.16	7.2		6.5		5.8						
35			35	3.57	8.4		7.6		6.7						
40			40	3.15	9.6		8.6		7.7						
45			45	2.77	10.8		9.7		8.6						
50			50	2.50	12.0		10.8		9.6						
55			55	2.27	13.2		11.9		10.6						
60			60	2.08	14.4		13.0		11.5						
65			65	1.92	15.6		14.0		12.5						
70			70	1.79	16.8		15.1		13.4						
75			75	1.67	18.0		16.2		14.4						
80	80	1.56	19.2	17.3	15.4										
90	90	1.39	21.6	19.4	17.3										
100	100	1.25	24.0	21.6	19.2										