CLASS 125 CAST BRONZE, GATE VALVES

Fig: 280/125S-BS-NR-NPT Sizes: 3/8-2inch(10-50mm)

SCREWED BONNET, INSIDE SCREW, NON RISING STEM, SCREWED ENDS.

Standards

. End to End: MANUFACTURERS STANDARD

. End Connection: ASME B1.20.1

. Wall Thickness: MANUFACTURERS STANDARD

Test Standard

. MANUFACTURERS STANDARD

Dimensions

SIZE(inch/	/mm)	L	L1	н	D1	Kg
3/8	10	43.0	0.0	87.0	48.0	0.00
1/2	15	49.0	0.0	93.0	55.0	0.00
3/4	20	53.0	0.0	111.0	63.0	0.00
1	25	61.0	0.0	127.0	70.0	0.00
11/4	32	64.0	0.0	145.0	80.0	0.00
11/2	40	68.0	0.0	170.0	90.0	0.00
2	50	74.0	0.0	189.0	100.0	0.00


Material List

NAME OF PART	MATERIAL	SPECIFICATION	
BODY	CAST BRONZE	B62	
BONNET	CAST BRONZE	B62	
STEM	CAST BRONZE	B62	
DISC	CAST BRONZE	B62	

Specifications

CLASS 125 CAST BRONZE, GATE VALVES, SCREWED BONNET, INSIDE SCREW, NON RISING STEM, SCREWED ENDS.

End to End: MANUFACTURERS STANDARD, End Connection: ASME B1.20.1, Wall Tchickness: MANUFACTURERS STANDARD, Test Standard: MANUFACTURERS STANDARD, Sizes: 3/8-2inch(10-50mm), BODYMATERIAL: CAST BRONZE, BONNETMATERIAL: CAST BRONZE, STEMMATERIAL: CAST BRONZE, DISCMATERIAL: CAST BRONZE, Fig: 280/125S-BS-NR-NPT



For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



